

**TECHNICAL DATA SHEET**  
**ANTISILICONE**The identification code: TPR-PRDAS10  
TPR-PRDAS50**PRODUCT DESCRIPTION**

Additive used to prevent the formation of silicone craters as a result of the deposition of silicone on layer of varnish. This causes breaking the surface tension forming cavities commonly known as "fish eyes". Ready to use. Usage by pouring and thorough mixing with varnish.

Please be aware, that silicones and other grease sticking contained in the varnish in a large amount can cause permanent deformation of the surface even using such additives.

**USAGE**

- one-component and two-component varnishes

**MIXING RATIO**

Amount of additive	Type of medium
up to 10%	ready-mix two-component paint with hardener
up to 10%	one-component paint
Comments:	Please be aware, when applied that 10% of the volume of paint and hardener do <u>not</u> use thinners. This additive in a sufficiently effective way decreases the viscosity of clearcoat.

**STORAGE TIME AND CONDITIONS**

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 12 months from date of manufacture - date on the top of container.

**HEALTH AND SAFETY REGULATIONS**

See Safety Data Sheet of the product.

**SPECIFIC WEIGHT**

About 845 g/l